



admiral[®]

Superior Marine Acrylic
Optimum weather Protection
from sunrise to sunset



Environmentally
Friendly



UV
Resistant

admiral[®]

admiral[®] 100% solution dyed acrylic has been engineered to withstand the rigours of the most extreme elements of salt, water and damaging rays of the sun.

admiral[®] from Defab is a superior marine acrylic guaranteed to deliver optimum weather protection from sunrise to sunset.











Applications

admiral[®] marine acrylic from Defab is the fabric of choice by experts who expect maximum protection from the everchanging elements.

Ideal for boat covers, bimini tops, marine and sail covers, flybridge enclosures, cockpit, tonneau, screens, outdoor furniture, cushions and market umbrellas.

Key features

Quality and Performance are surnomomous with admiral[®] marine acrylic

-  Environmentally friendly
-  100% Blockout UV rays
-  Unsurpassed Colour Stability
-  High Resistance to light and atmospheric conditions
-  Mildew and mould resistant
-  Superior water repellance
-  Highly breathable
-  Shrink proof
-  Maximum tear resistance
-  Guarantee 5 years

Defab guarantee limited to the replacement of fabric.
For further details refer to Defab guarantee form.

 **defab[®]**

admiral®

Solid Colours 100% solution dyed acrylic



Disclaimer: Colours printed are a colour indication reference only. Please refer to actual admiral fabric sample.

Easy to clean

admiral®

There are 5 basic tips to ensure that admiral marine acrylic from Defab provides durability longevity and servicability.

1. Vacuum off any dirt regularly.
2. If necessary, clean with a neutral mild soap and sponge, with water at a temperature of no more than 30 deg. Rinse with water and allow to dry for at minimum of 30 minutes.
3. Do not use abrasive products or chemicals.
4. Always let the fabric dry completely before rolling it up, stowing or folding it away.
5. If possible store appropriately away in a cover when not in use.

The better you care for your admiral marine acrylic, the longer you will be able to maintain its lustre.

Information

admiral®

Weight	300 gsm	Tensile Strength (Warp)	1400 N/5 cm
Width	200 cm	Water Resistance (Spray Rating)	95 N/5 cm
Finish	DuPont Teflon Nanotechnology	Light Fastness (Min)	100
Roll Length	50 mts	Warranty	5 years
Roll Weight (Nominal)	30 kg		



Quality Endorsed Company
ISO 9001 LIC5045
Standards Australia



UPF rating



Head Office 28-30 Somerton Park Drive
Campbellfield Vic, 3061 Australia
Local Sales: 1300 785 322
Tel: +61 3 9305 3988 Fax: +61 3 9305 1377
Email: canvas@defab.com.au
www.defab.com.au

Whilst every attempt has been made, slight colour variations may occur between these representations and actual Defab Canvas fabrics. No printing process can capture the true brilliance of Defab colours. Defab® and somerton® canvas are Registered Trademarks of Defab Weavers Pty. Ltd. Defab Weavers Pty Ltd ACN 005 189 319

